AutoSeal® 2150 Series

PRODUCTION PRESSURE SEALERS





- Designed for continuous, high production environments
- Automatic, touchscreen job setup
- 2 and 6 automatic fold plate configurations
- Unlimited monthly duty cycle

FORMAX®

www.formax.com

Local Dealer:

Automated Mailroom
6201 Johns Road, Ste 12
Tampa, FL 33634-4434
(877) 870-6805 – (813) 870-6805
AutomatedMailroom.com


The **AutoSeal® 2150 Series Production Pressure Sealer** is designed to process high-volume jobs up to 27,000 forms per hour, with an **unlimited monthly duty cycle**. The graphics-based **12" color touchscreen is mounted on a swivel arm**, and provides intuitive control of fold type, form length and operating speed. Users can program **up to 200 custom jobs**, and process **forms up to 17" wide and 26" long**. Two configurations are available, each with a pile feeder input: the **FD 2150** with 2 automatic fold plates, and the **FD 2156** with 6 automatic fold plates. **Fully automated settings** include the feeder, transport deck, fold plate stops, deflectors and fold rollers. Standard features include **heavy-duty fold plates, steel-and-urethane fold rollers, safety interlocks, jam detection, and addition/batch counter**. Options include the V-Stack36i Vertical Stacker.




High-Capacity Pile Feeder
High-capacity elevating deck holds up to 3,500 forms



Top-Feed Suction System
Delivers precise, high-speed feeding for consistent throughput




Outfeed Ball Deck
Efficiently transfers forms from fold plates to pressure seal rollers



Auto-Adjust Transport Deck
Automatically adapts to different form widths



12-inch Color Touchscreen
Graphics-based and designed for easy walk-up use



Optional V-Stack36i Stacker
Vertically stacks up to 22" of folded documents for easy unloading

STANDARD FEATURES

- Two configurations available
- Processes up to 27,000 forms per hour
- 12" color touchscreen control panel
- Handles forms up to 17" wide x 26" long
- Fully automated settings
- Automatically adjusting infeed transport deck
- High-capacity elevating pile feeder
- Pre-programmed with 20 standard folds
- Stores up to 200 custom jobs
- Addition and batch counters
- Safety interlocks
- Rugged combination rollers
- Insulated fold plates for noise reduction
- Jam detection
- Static eliminator

OPTIONS

- V-Stack36i Vertical Output Stacker
- 2200-15 Data Integrity Scanning System-Sequence Check & Document Verification
- 402 Series Jogger

SPECIAL NOTES

- Customer-supplied fork lift is required for installation and setup
- Three phase power is required.

SPECIFICATIONS

Pile Feeder Capacity	Up to 3,500 forms
Variable Speed	Up to 27,000 sheets per hour
Duty Cycle	Unlimited
Fold Plates	**FD 2150:** 2 fold plate system **FD 2156:** 6 fold plate system
Form Size	Up to 17" W x 26" L (432 x 660mm)
Dimensions*	**FD 2150:** 137.5" L x 68" D x 57.4" H (349 x 173 x 148cm) **FD 2156:** 137.5" L x 68" D x 57.4" H (349 x 173 x 148cm)
Vacuum Pump	Standard, external
Weight	Approximately 1,364 lbs (619kg)
Power	3-phase 200-220V, 50/60 Hz
Power Plug	NEMA L15-20P plug included, NEMA L15-20R receptacle required